### 40 CFR Ch. I (7-1-12 Edition)

## Pt. 63, Subpt. MMMM, Table 2

For the following device	You must meet the following operating limit	And you must demonstrate continuous compliance with the operating limit by
	b. The temperature of the carbon bed, after completing each regeneration and any cooling cycle, must not exceed the carbon bed temperature limit established according to § 63.3967(c).	i. Measuring the temperature of the carbon bed after completing each regeneration and any cooling cycle according to § 63.3968(d); and ii. Operating the carbon beds such that each carbon bed is not returned to service until completing each regeneration and any cooling cycle until the recorded temperature of the carbon bed is at or below the temperature limit.
4. Condenser	The average condenser outlet (product side) gas temperature in any 3-hour period must not exceed the temperature limit established according to § 63.3967(d).	iii. Collecting the condenser outlet (product side) gas temperature according to § 63.3968(e); ii. Reducing the data to 3-hour block averages; and iii. Maintaining the 3-hour average gas temperature at the outlet at or below the temperature limit.
<ol> <li>Concentrators, includ- ing zeolite wheels and rotary carbon adsorbers.</li> </ol>	The average gas temperature of the desorption concentrate stream in any 3-hour period must not fall below the limit established according to §63.3967(e); and	i. Collecting the temperature data according to 63.3968(f);     ii. Reducing the data to 3-hour block averages; and     iii. Maintaining the 3-hour average temperature at or above the temperature limit.
	b. The average pressure drop of the dilute stream across the concentrator in any 3-hour period must not fall below the limit established according to § 63.3967(e).	i. Collecting the pressure drop data according to 63.3968(f);     ii. Reducing the pressure drop data to 3-hour block averages; and     iii. Maintaining the 3-hour average pressure drop
6. Emission capture system that is a PTE according to § 63.3965(a).	The direction of the air flow at all times must be into the enclosure; and either	at or above the pressure drop limit.  i. Collecting the direction of air flow, and either the facial velocity of air through all natural draft openings according to \$63.3968(b)(1) or the pressure drop across the enclosure according to \$63.3968(g)(2); and  ii. Maintaining the facial velocity of air flow through all natural draft openings or the pressure drop at or above the facial velocity limit or pressure drop limit, and maintaining the direction of air flow into the enclosure at all times.
	b. The average facial velocity of air through all natural draft openings in the enclosure must be at least 200 feet per minutes; or c. The pressure drop across the enclosure must be at least 0.007 inch H <sub>2</sub> O, as established in	i. See items 6.a.i and 6.a.ii. i. See items 6.a.i and 6.a.ii.
7. Emission capture system that is not a PTE according to § 63.3965(a).	Method 204 of appendix M to 40 CFR part 51.  a. The average gas volumetric flow rate or duct static pressure in each duct between a capture device and add-on control device inlet in any 3-hour period must not fall below the average volumetric flow rate or duct static pressure limit established for that capture device according to § 63.3967(f).	i. Collecting the gas volumetric flow rate or duct static pressure for each capture device according to § 63.3968(g); ii. Reducing the data to 3-hour block averages; and iii. Maintaining the 3-hour average gas volumetric flow rate or duct static pressure for each capture device at or above the gas volumetric flow rate or duct static pressure limited.

# Table 2 to Subpart MMMM of Part 63—Applicability of General Provisions to Subpart MMMM of Part 63

You must comply with the applicable General Provisions requirements according to the following table:

Citation	Subject	Applicable to subpart MMMM	Explanation
§ 63.1(a)(1)–(14) § 63.1(b)(1)–(3)			Applicability to subpart MMMM is also specified in §63.3881.
§ 63.1(c)(1)	Applicability After Standard Established.	Yes.	<b>0</b>
§ 63.1(c)(2)–(3)	Applicability of Permit Program for Area Sources.	No	Area sources are not subject to subpart MMMM.
§ 63.1(c)(4)–(5)	Extensions and Notifications	Yes.	

# **Environmental Protection Agency**

# Pt. 63, Subpt. MMMM, Table 2

Citation	Subject	Applicable to subpart MMMM	Explanation
§ 63.1(e)	Applicability of Permit Program Before Relevant Standard is Set.	Yes.	
§ 63.2		Yes	Additional definitions are specified in § 63.3981.
§ 63.1(a)–(c)	Units and Abbreviations	Yes.	1100 111 3 00.0001.
§ 63.4(a)(1)–(5)		Yes.	
§ 63.4(b)–(c)		Yes.	
§ 63.5(a)		Yes.	
§ 63.5(b)(1)–(6)	Constructed, and Reconstructed Sources.	Yes.	
§ 63.5(d)	struction/Reconstruction.	Yes.	
§ 63.5(e)	struction.	Yes.	
§ 63.5(f)	Approval of Construction/Reconstruction Based on Prior State Review.	Yes.	
§ 63.6(a)	Compliance With Standards and Maintenance Requirements—Applicability.	Yes.	
§ 63.6(b)(1)–(7)		Yes	Section 63.3883 specifies the compliance dates.
§ 63.6(c)(1)–(5)	Compliance Dates for Existing Sources.	Yes	Section 63.3883 specifies the compliance dates.
§ 63.6(e)(1)–(2) § 63.6(e)(3)		Yes. Yes	Only sources using an add-on control device to comply with the standard must complete startup, shutdown, and mal-
§ 63.6(f)(1)	Compliance Except During Start- up, Shutdown, and Malfunc- tion.	Yes	function plans.  Applies only to sources using an add-on control device to comply with the standard.
§ 63.6(f)(2)–(3)		Yes.	pry with the standard.
§ 63.6(g)(1)–(3) § 63.6(h)		Yes. No	Subpart MMMM does not estab- lish opacity standards and does not require continuous opacity monitoring systems (COMS).
§ 63.6(i)(1)–(16) § 63.6(j)		Yes. Yes.	, ,
§ 63.7(a)(1)		Yes	Applies to all affected sources. Additional requirements for performance testing are specified in §§ 63.3964, 63.3965, and 63.3966.
§ 63.7(a)(2)	Performance Test Requirements—Dates.	Yes	Applies only to performance tests for capture system and control device efficiency at sources using these to comply with the standard. Section 63.3960 specifies the schedule for performance test requirements that are earlier than those specified in §63.7(a)(2).
§ 63.7(a)(3)	Performance Tests Required By the Administrator.	Yes.	
§ 63.7(b)–(e)		Yes	Applies only to performance tests for capture system and add-on control device effi- ciency at sources using these to comply with the standard.
§ 63.7(f)	S S	Yes	Applies to all test methods except those used to determine capture system efficiency.

## Pt. 63, Subpt. MMMM, Table 2

Citation	Subject	Applicable to subpart MMMM	Explanation
§ 63.7(g)–(h)	Performance Test Require- ments—Data Analysis, Rec- ordkeeping, Reporting, Waiver of Test.	Yes	Applies only to performance tests for capture system and add-on control device efficiency at sources using these to comply with the standard.
§ 63.8(a)(1)-(3)	Monitoring Requirements—Applicability.	Yes	Applies only to monitoring of capture system and add-on control device efficiency at sources using these to comply with the standard. Additional requirements for monitoring are specified in § 63.3968.
§ 63.8(a)(4)	Additional Monitoring Requirements.	No	Subpart MMMM does not have monitoring requirements for flares.
§ 63.8(c)(1)—(3)	Conduct of Monitoring	Yes. Yes	Applies only to monitoring of capture system and add-on control device efficiency at sources using these to comply with the standard. Additional requirements for CMS operations and maintenance are specified in § 63.3968.
§ 63.8(c)(4)	CMS	No	§63.3968 specifies the require- ments for the operation of CMS for capture systems and add-on control devices at sources using these to com- ply.
§ 63.8(c)(5)	COMS	No	Subpart MMMM does not have opacity or visible emission standards.
§ 63.8(c)(6)	CMS Requirements	No	Section 63.3968 specifies the requirements for monitoring systems for capture systems and add-on control devices at sources using these to comply.
§ 63.8(c)(7) § 63.8(c)(8)	CMS Out-of-Control Periods CMS Out-of-Control Periods and	Yes. No	§63.3920 requires reporting of
§ 63.8(d)–(e)	Reporting. Quality Control Program and CMS Performance Evaluation.	No	CMS out-of-control periods. Subpart MMMM does not require the use of continuous
§ 63.8(f)(1)–(5)	Use of an Alternative Monitoring	Yes.	emissions monitoring systems.
§ 63.8(f)(6)	Method. Alternative to Relative Accuracy Test.	No	Subpart MMMM does not require the use of continuous
§ 63.8(g)(1)–(5)	Data Reduction	No	emissions monitoring systems. Sections 63.3967 and 63.3968 specify monitoring data reduction.
§ 63.9(a)-(d) § 63.9(e)	Notification Requirements Notification of Performance Test	Yes. Yes	Applies only to capture system and add-on control device performance tests at sources using these to comply with the
§ 63.9(f)	Notification of Visible Emissions/ Opacity Test.	No	standard. Subpart MMMM does not have opacity or visible emissions standards.
§ 63.9(g)(1)–(3)	Additional Notifications When Using CMS.	No	Subpart MMMM does not require the use of continuous emissions monitoring systems.
§ 63.9(h)	Notification of Compliance Status.	Yes	Section 63.3910 specifies the dates for submitting the notification of compliance status.
§ 63.9(i)	Adjustment of Submittal Dead- lines.	Yes.	
§ 63.9(j)	Change in Previous Information	Yes.	

#### **Environmental Protection Agency**

#### Pt. 63, Subpt. MMMM, Table 3

Citation	Subject	Applicable to subpart MMMM	Explanation
§ 63.10(a)	Recordkeeping/Reporting—Applicability and General Information.	Yes.	
§ 63.10(b)(1)	General Recordkeeping Requirements.	Yes	Additional requirements are specified in §§ 63.3930 and 63.3931.
§ 63.10(b)(2) (i)–(v)	Recordkeeping Relevant to Startup, Shutdown, and Mal- function Periods and CMS.	Yes	Requirements for startup, shut- down, and malfunction records only apply to add-on control devices used to com- ply with the standard.
§ 63.10(b)(2) (vi)–(xi)		Yes.	
§ 63.10(b)(2) (xii)	Records	Yes.	
§ 63.10(b)(2) (xiii)		No	Subpart MMMM does not re- quire the use of continuous emissions monitoring systems.
§ 63.10(b)(2) (xiv)		Yes.	
§ 63.10(b)(3)	Recordkeeping Requirements for Applicability Determinations.	Yes.	
§ 63.10(c) (1)–(6)	Additional Recordkeeping Requirements for Sources with CMS.	Yes.	
§ 63.10(c) (7)–(8)		No	The same records are required in §63.3920(a)(7).
§63.10(c) (9)-(15)		Yes.	
§ 63.10(d)(1)	General Reporting Requirements.	Yes	Additional requirements are specified in § 63.3920.
§ 63.10(d)(2)	Report of Performance Test Results.	Yes	Additional requirements are specified in § 63.3920(b).
§ 63.10(d)(3)	Reporting Opacity or Visible Emissions Observations.	No	Subpart MMMM does not require opacity or visible emissions observations.
§ 63.10(d)(4)	Progress Reports for Sources With Compliance Extensions.	Yes.	
§ 63.10(d)(5)	Startup, Shutdown, and Malfunction Reports.	Yes	Applies only to add-on control devices at sources using these to comply with the standard.
§ 63.10(e) (1)–(2)	Additional CMS Reports	No	Subpart MMMM does not require the use of continuous emissions monitoring systems.
§ 63.10(e) (3)	Excess Emissions/CMS Performance Reports.	No	Section 63.3920 (b) specifies the contents of periodic compliance reports.
§ 63.10(e) (4)	COMS Data Reports	No	Subpart MMMMM does not specify requirements for opacity or COMS.
§ 63.10(f)	Recordkeeping/Reporting Waiver.	Yes.	ity of Golwio.
§ 63.11	Control Device Requirements/ Flares.	No	Subpart MMMM does not speci- fy use of flares for compli- ance.
§ 63.12	State Authority and Delegations	Yes.	
§ 63.13	Addresses	Yes.	
§ 63.14	Incorporation by Reference	Yes.	
§ 63.15	Availability of Information/Confidentiality.	Yes.	

Table 3 to Subpart MMMM of Part 63—Default Organic HAP Mass Fraction for Solvents and Solvent Blends

You may use the mass fraction values in the following table for solvent blends for which you do not have test data or manufacturer's formulation data and which match either the solvent blend name or the chemical abstract series (CAS) number. If a solvent blend matches both the name and CAS number for an entry, that entry's organic HAP mass fraction must be used for that solvent blend. Otherwise, use the organic HAP mass fraction for the entry matching either the solvent blend name or CAS number, or use the organic HAP mass fraction from table 4 to this subpart if neither the name or CAS number match.